

Printing date 08/28/2018 Review date 08/28/2018

#### 1 Identification

- · Product identifier
- · Trade name: AFT Multi Element Solution
- · Article number N8145061
- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc.

710 Bridgeport Avenue

Shelton, Connecticut 06484 USA

CustomerCareUS@perkinelmer.com

203-925-4600

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

### 2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

*P264* Wash thoroughly after handling.

*P280* Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water. P321 Specific treatment (see on this label).

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 0Reactivity = 0

(Contd. on page 2)



*Printing date 08/28/2018* Review date 08/28/2018

# Trade name: AFT Multi Element Solution

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)



2 Health = 2Fire = 0

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formal dehydes.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

Hazardous d	components:	
7697-37-2	Nitric Acid Ox	2.09 in Corr. 1A, H314
Additional (	Components	
7439-92-1	lead Acute Tox. 3, H301 Carc. 2, H351; Repr. 1A, H360-H362 Acute Tox. 4, H332	0.002%
7440-17-7	rubidium  Water-react. 1, H260  Skin Corr. 1B, H314; Eye Dam. 1, H318	0.002%
7782-49-2	selenium  Acute Tox. 3, H301; Acute Tox. 3, H331  STOT RE 2, H373	0.002%
7440-24-6	strontium  Mater-react. 1, H260	0.002%
7440-61-1		0.002%
7440-62-2	vanadium	0.002%
7440-66-6	zinc  Water-react. 2, H261	0.002%
7440-48-4	cobalt <b>♦</b> Resp. Sens. 1, H334; Carc. 2, H351 <b>↑</b> Skin Sens. 1, H317	0.0002%
7440-47-3	chromium	0.0002%
14644-55-4	cesium vanadium trioxide	0.0002%
7440-50-8	copper	0.0002%



Printing date 08/28/2018 Review date 08/28/2018

# Trade name: AFT Multi Element Solution

7.120.00.5		(Contd. of pag
7439-89-6		0.0002
7440-55-3	gallium Skin Corr. 1C, H314	0.0002
7440-74-6	Indium	0.0002
7440-09-7	potassium  Water-react. 1, H260 Skin Corr. 1B, H314	0.00029
7439-93-2	lithium  Water-react. 1, H260 Skin Corr. 1B, H314	0.00029
7439-95-4	magnesium  Pyr. Sol. 1, H250; Water-react. 1, H260	0.00029
7439-96-5	manganese	0.0002
7440-23-5		0.0002
7440-02-0	nickel  Carc. 2, H351; STOT RE 1, H372  Skin Sens. 1, H317	0.0002
7429-90-5	aluminium	0.0002
7440-38-2	Arsenic	0.0002
7440-39-3	barium  Water-react. 2, H261	0.0002
7440-41-7	beryllium  Acute Tox. 3, H301; Acute Tox. 2, H330 Carc. 1B, H350; STOT RE 1, H372 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.00029
7440-28-0	thallium  Acute Tox. 2, H300; Acute Tox. 2, H330  STOT RE 2, H373	0.00029
7440-69-9	bismuth	0.0002
7440-70-2	calcium  Water-react. 2, H261	0.0002
7440-43-9	cadmium (non-pyrophoric)  → Acute Tox. 2, H330  → Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361; STOT RE 1, H372	0.00029
7440-22-4	silver	0.0002
7732-18-5	Water	97.9816



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 3)

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 Nitric Acid	0.16 ppm
7439-92-1 lead	$0.15 \text{ mg/m}^3$
7440-17-7 rubidium	$3.9 \text{ mg/m}^3$
7782-49-2 selenium	$0.6 \text{ mg/m}^3$
7440-24-6 strontium	$30 \text{ mg/m}^3$
7440-61-1 uranium	$0.6 \text{ mg/m}^3$
7440-62-2 vanadium	$3 mg/m^3$
7440-66-6 zinc	6 mg/m <sup>3</sup>
7440-48-4 cobalt	$0.18 \text{ mg/m}^3$
7440-47-3 chromium	$1.5 mg/m^3$
<u>'</u>	(Contd. on pag

on page 3)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

7440-50-8 copper	(Contd. of page 3 mg/m³
7439-89-6 iron	$3.2 \text{ mg/m}^3$
7440-55-3 gallium	$30 \text{ mg/m}^3$
7440-74-6 Indium	$0.3 \text{ mg/m}^3$
7440-09-7 potassium	$2.3 \text{ mg/m}^3$
7439-93-2 lithium	$3.3 \text{ mg/m}^3$
7439-95-4 magnesium	$18 \text{ mg/m}^3$
7439-96-5 manganese	$3 \text{ mg/m}^3$
7440-23-5 sodium	13 mg/m³
7440-02-0 nickel	$4.5 \text{ mg/m}^3$
7440-38-2 Arsenic	$1.5 \text{ mg/m}^3$
7440-39-3 barium	$1.5 \text{ mg/m}^3$
7440-41-7 beryllium	0.0023 mg/n
7440-28-0 thallium	$0.06 \text{ mg/m}^3$
7440-69-9 bismuth	$15 \text{ mg/m}^3$
7440-43-9 cadmium (non-pyrophoric)	$0.10 \text{ mg/m}^3$
7440-22-4 silver	$0.3 \text{ mg/m}^3$
PAC-2:	
7697-37-2 Nitric Acid	24 ppm
7439-92-1 lead	$120 \text{ mg/m}^3$
7440-17-7 rubidium	$43 \text{ mg/m}^3$
7782-49-2 selenium	$6.6 \text{ mg/m}^3$
7440-24-6 strontium	$330 \text{ mg/m}^3$
7440-61-1 uranium	$5 mg/m^3$
7440-62-2 vanadium	$5.8 \text{ mg/m}^3$
7440-66-6 zinc	$21 \text{ mg/m}^3$
7440-48-4 cobalt	$2 mg/m^3$
7440-47-3 chromium	$17 \text{ mg/m}^3$
7440-50-8 copper	$33 \text{ mg/m}^3$
7439-89-6 iron	$35 \text{ mg/m}^3$
7440-55-3 gallium	$330 \text{ mg/m}^3$
7440-74-6 Indium	$3.3 \text{ mg/m}^3$
7440-09-7 potassium	$25 \text{ mg/m}^3$
7439-93-2 lithium	$36 \text{ mg/m}^3$
7439-95-4 magnesium	$200 \text{ mg/m}^3$
7439-96-5 manganese	$5 \text{ mg/m}^3$
7440-23-5 sodium	$140 \text{ mg/m}^3$
7440-02-0 nickel	$50 \text{ mg/m}^3$
7440-38-2 Arsenic	$17 \text{ mg/m}^3$
7440-39-3 barium	$180 \text{ mg/m}^3$



Printing date 08/28/2018 Review date 08/28/2018

### Trade name: AFT Multi Element Solution

740 41 711 111	(Contd. of pa
7440-41-7 beryllium	0.025 mg.
7440-28-0 thallium	3.3 mg/m
7440-69-9 bismuth	170 mg/m
7440-43-9 cadmium (non-pyrophoric)	0.76 mg/n
7440-22-4 silver	170 mg/m
· PAC-3:	
7697-37-2 Nitric Acid	92 ppm
7439-92-1 lead	700 mg/m
7440-17-7 rubidium	260 mg/m
7782-49-2 selenium	40 mg/m <sup>3</sup>
7440-24-6 strontium	2,000 mg.
7440-61-1 uranium	$30 \text{ mg/m}^3$
7440-62-2 vanadium	$35 \text{ mg/m}^3$
7440-66-6 zinc	120 mg/m
7440-48-4 cobalt	$20 \text{ mg/m}^3$
7440-47-3 chromium	99 mg/m³
7440-50-8 copper	200 mg/m
7439-89-6 iron	150 mg/m
7440-55-3 gallium	2,000 mg.
7440-74-6 Indium	$20 \text{ mg/m}^3$
7440-09-7 potassium	150 mg/m
7439-93-2 lithium	220 mg/m
7439-95-4 magnesium	1,200 mg
7439-96-5 manganese	1,800 mg.
7440-23-5 sodium	870 mg/m
7440-02-0 nickel	99 mg/m³
7440-38-2 Arsenic	100 mg/m
7440-39-3 barium	1,100 mg.
7440-41-7 beryllium	0.1 mg/m
7440-28-0 thallium	$20 \text{ mg/m}^3$
7440-69-9 bismuth	990 mg/m
7440-43-9 cadmium (non-pyrophoric)	4.7 mg/m
7440-22-4 silver	990 mg/m

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.

(Contd. on page 7)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 6)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 7697-37-2 Nitric Acid

- PEL Long-term value: 5 mg/m³, 2 ppm

  REL Short-term value: 10 mg/m³, 4 ppm

  Long-term value: 5 mg/m³, 2 ppm

  TLV Short-term value: 10 mg/m³, 4 ppm

  Long-term value: 5.2 mg/m³, 2 ppm
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 7)

· Eye protection:



Tightly sealed goggles or safety glasses

Information on basic physical and o	chemical properties	
General Information	nemcui properties	
Appearance:		
Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	e <b>r):</b> Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	98.0 %	
VOC content:	0.00 %	

(Contd. on page 9)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 8)

· Other information

No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
7439-92-1	lead	28
7782-49-2	selenium	3
7440-48-4	cobalt	28
7440-47-3	chromium	3
7440-02-0	nickel	28
7440-38-2	Arsenic	1
7440-41-7	beryllium	1
7440-43-9	cadmium (non-pyrophoric)	1
· NTP (Nati	onal Toxicology Program)	
7439-92-1	lead	R
7440-48-4	cobalt	R
7440-02-0	nickel	R
7440-38-2	Arsenic	K
7440-41-7	beryllium	K
7440-43-9	cadmium (non-pyrophoric)	K
· OSHA-Ca	(Occupational Safety & Health Administration)	·
7440-38-2	Arsenic	

(Contd. on page 10)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 9)

7440-43-9 cadmium (non-pyrophoric)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

/	TO COL	000	0 101	770	1010	$m \sim 11$	tion
-		IRTI	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			,,,,,,	,,,,,,

· UN-N	umber	•	
. DOT	ADD	IMDC	TATA

· DOT, ADR, IMDG, IATA UN3264

· UN proper shipping name

• **DOT**Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid)
• **ADR**3264 Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

- · Transport hazard class(es)
- $\cdot DOT$



Class 8 Corrosive substances

(Contd. on page 11)



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

	(Contd. of page
Label	8
ADR	
^	
B	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
\$\times \text{\$\times \text{\$\text{\$\text{\$\color{100}{100}}}}	
▼ CI	
Class Label	8 Corrosive substances 8
	•
Packing group DOT, ADR, IMDG, IATA	III
	***
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Acids
Stowage Cade	A SW2 Clear of living quarters
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	
	Not applicable.
Transport/Additional information:	
DOT	0
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
4 D D	On cargo aircraft only. 00 L
ADR Excepted quantities (EQ)	Code: E1
Excepted quantutes (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	<i>5L</i>
Excepted quantities $(\widetilde{EQ})$	Code: E1
- -	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 11)

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID), 8, III

7732-18-5	alth and environmental regulations Water		97.98169
7697-37-2	Nitric Acid	© Ox. Liq. 2, H272 Skin Corr. 1A, H314	2.0%
7440-17-7	rubidium	<ul> <li>Water-react. 1, H260</li> <li>Skin Corr. 1B, H314; Eye Dam. 1, H318</li> </ul>	0.002%
Sara			
Section 35.	5 (extremely hazardous substances	):	
7697-37-2	Nitric Acid		
Section 31.	3 (Specific toxic chemical listings).	•	
	2 Nitric Acid		
7439-92-	l lead		
7782-49-2	2 selenium		
7440-62-2	2 vanadium		
7440-66-6	5 zinc		
7440-48-4	4 cobalt		
7440-47	3 chromium		
14644-55-4	4 cesium vanadium trioxide		
7440-50-6	8 copper		
7439-96	5 manganese		
7440-02-0	nickel		
7429-90	5 aluminium		
7440-38-2	2 Arsenic		
7440-39			
	7 beryllium		
	thallium thallium		
	g cadmium (non-pyrophoric)		
7440-22-			
	xic Substances Control Act):		
_	ents are listed.		
7439-92-	Nitric Acid		
	i   ieaa 7   rubidium		
	rubiaium 2 selenium		
//02-49-2	z   seienium		



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

7440 41	(Contd. of pag	зe
7440-61-1		_
	vanadium	
7440-66-6		
7440-48-4		
	chromium	
	cesium vanadium trioxide	
7440-50-8	<u> </u>	
7439-89-6		
7440-55-3		
7440-74-6		
7440-09-7	potassium	
7439-93-2	lithium	
	magnesium	
7439-96-5	manganese	
7440-23-5	sodium	_
7440-02-0	nickel	_
7429-90-5	aluminium	_
7440-38-2	Arsenic	_
7440-39-3	barium	_
7440-41-7	beryllium	_
7440-28-0		_
7440-69-9	bismuth	_
7440-70-2	calcium	_
7440-43-9	cadmium (non-pyrophoric)	_
7440-22-4		_
· Proposition		_
_	known to cause cancer:	_
7439-92-1		_
7440-48-4		_
7440-02-0		_
7440-38-2		_
7440-41-7		-
	cadmium (non-pyrophoric)	_
		=
	known to cause reproductive toxicity for females:	_
7439-92-1		_
	known to cause reproductive toxicity for males:	
7439-92-1		
7440-43-9	cadmium (non-pyrophoric)	
· Chemicals	known to cause developmental toxicity:	_
7439-92-1	<u> </u>	_



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

7440-43-9	cadmium (non-pyrophoric)	(Contd. of page
Cancerogei	nity categories	
_	conmental Protection Agency)	
7439-92-1	lead	B2
7782-49-2	selenium	D
7440-66-6	zinc	D, I, II
7440-47-3	chromium	D
7440-50-8	copper	D
7439-96-5	manganese	D
7440-38-2	Arsenic	A
7440-39-3	barium	D, CBD(inh), NL(oral)
7440-41-7	beryllium	B1, K/L(inh), CBD(ord
7440-43-9	cadmium (non-pyrophoric)	BI
7440-22-4	silver	D
TLV (Thres	hold Limit Value established by ACGIH)	
7439-92-1	lead	
7440-61-1	uranium	
7440-48-4	cobalt	
7440-47-3	chromium	
7440-02-0 nickel		
7429-90-5	aluminium	
7440-38-2 Arsenic		
7440-39-3	7440-39-3 barium	
7440-41-7	beryllium	A
7440-43-9	cadmium (non-pyrophoric)	
NIOSH-Ca	(National Institute for Occupational Safety and Heal	(th)
7440-61-1	uranium	
7440-02-0	nickel	
7440-38-2	Arsenic	
7440-41-7	beryllium	
7440-43-9	cadmium (non-pyrophoric)	

### · National regulations:

### · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Water hazard class: Generally not hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

USA



Printing date 08/28/2018 Review date 08/28/2018

Trade name: AFT Multi Element Solution

(Contd. of page 14)

# 16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids - Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

\* \* Data compared to the previous version altered.

USA