

USA

acc. to OSHA HCS

Printing date 10/08/2018

Review date 10/08/2018

1 Identification · Product identifier · Trade name: LITHIUM 1000 PPM A/S STANDARD • Article number N9300129 · Application of the substance / the mixture Laboratory chemicals · Details of the supplier of the safety data sheet · Manufacturer/Supplier: PerkinElmer, Inc. 710 Bridgeport Avenue Shelton, Connecticut 06484 USA CustomerCareUS@perkinelmer.com 203-925-4600 • Emergency telephone number: CHEMTREC (within US) 800-424-9300 CHEMTREC (from outside US) +1 703-527-3887 (call collect) CHEMTREC (within AU) +(61)-290372994 2 Hazard(s) identification · Classification of the substance or mixture Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS07 · Signal word Warning · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. · Precautionary statements P264 Wash thoroughly after handling. P280 Wear protective gloves / eye protection / face protection. P302+P352 If on skin: Wash with plenty of water. Specific treatment (see on this label). P321 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. *P332+P313* Take off contaminated clothing and wash it before reuse. *P362+P364* P337+P313 If eye irritation persists: Get medical advice/attention. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 0Reactivity = 0(Contd. on page 2)



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 1)

• HMIS-ratings (scale 0 - 4)

HEALTH2Health = 2FIRE \bigcirc Fire = 0REACTIVITY \bigcirc Reactivity = 0

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- 7732-18-5 Water
- · Identification number(s)
- **EC number:** 231-791-2
- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

• Hazardous	components:		
7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	1%
• Additional	Components		
7439-93-2	lithium	Water-react. 1, H260 Skin Corr. 1B, H314	%
7732-18-5	Water	97.9	%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 Nitric Acid	0.16 ppm
7439-93-2 lithium	3.3 mg/m ³
· PAC-2:	
7697-37-2 Nitric Acid	24 ppm
7439-93-2 lithium	36 mg/m ³
· PAC-3:	
7697-37-2 Nitric Acid	92 ppm
7439-93-2 lithium	220 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

USA



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

7697-37-2 Nitric Acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

• Breathing equipment: Not required.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles or safety glasses

(Contd. on page 5)

(Contd. of page 3)



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 4)

· Information on basic physical and c	hemical properties
· General Information	nemicui properties
· Appearance:	
Form:	Liquid
Color:	Transparent
· Odor:	Odorless
· Odor threshold:	Not determined.
pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	0 °C (32 °F)
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	23 hPa (17.3 mm Hg)
• Density at 20 •C (68 •F):	1 g/cm ³ (8.345 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Water:	97.9 %
VOC content:	0.00 %
Solids content:	0.1 %
• Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)

USA



Printing date 10/08/2018

Review date 10/08/2018

(Contd. of page 5)

Trade name: LITHIUM 1000 PPM A/S STANDARD

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 6)

USA

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

• **Recommendation:** Disposal must be made according to official regulations. • **Recommended cleansing agent:** Water, if necessary with cleansing agents.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
·DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NURIC ACU
· Transport hazard class(es)	
·DOT	
CORROSIVE 0	
· Class	8 Corrosive substances
· Label	8
· <i>ADR</i>	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
· Class	8 Corrosive substances
· Label	8
· Packing group · DOT, ADR, IMDG, IATA	111

[·] Uncleaned packagings:



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

	(Contd. of page
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F-A,S-B
Segregation groups	Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID), 8, III

*

\cdot Safety, health and environmental regulations/legislation specific for the substance or mixture					
7732-18-5	Water		97.9%		
7697-37-2	Nitric Acid	🔞 Ox. Liq. 2, H272 Skin Corr. 1A, H314	2.0%		
7439-93-2	lithium	Water-react. 1, H260 Skin Corr. 1B, H314	0.1%		
Sara		·			
Section 35.	5 (extremely hazardous substances):				
7697-37-2	Nitric Acid				
Section 31	3 (Specific toxic chemical listings):				
7697-37-2	Nitric Acid				
TCCA (Ta	cic Substances Control Act):				



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 8)

7697-37-2 Nitric Acid

7439-93-2 lithium 7732-18-5 Water

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

• Water hazard class: Generally not hazardous for water.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

• Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)



Printing date 10/08/2018

Review date 10/08/2018

Trade name: LITHIUM 1000 PPM A/S STANDARD

(Contd. of page 9)

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Ox. Liq. 2: Oxidizing liquids – Category 2 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A • * Data compared to the previous version altered. US A