

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

1 Identification

- **Product identifier**
- **Trade name:** STANDARD 25 MULTI-ELEMENT- 100mL
- **Article number** N9308543
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric Acid

- **Hazard statements**

H314 Causes severe skin burns and eye damage.

- **Precautionary statements**

- P260 Do not breathe dusts or mists.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.

(Contd. on page 2)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Hazardous components:**

| | | | |
|-----------|-------------|---|------|
| 7697-37-2 | Nitric Acid | Ox. Liq. 2, H272 Skin Corr. 1A, H314 | 5.0% |
|-----------|-------------|---|------|

- **Additional Components**

| | | | |
|-----------|--|--|-------|
| 7440-42-8 | boron | | 0.01% |
| | Acute Tox. 3, H301 | | |
| 7440-39-3 | barium | | 0.01% |
| | Water-react. 2, H261 | | |
| 7440-41-7 | beryllium | | 0.01% |
| | Acute Tox. 3, H301; Acute Tox. 2, H330 Carc. 1B, H350; STOT RE 1, H372 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 | | |
| 7440-69-9 | bismuth | | 0.01% |
| 7440-70-2 | calcium | | 0.01% |
| | Water-react. 2, H261 | | |
| 7440-43-9 | cadmium (non-pyrophoric) | | 0.01% |
| | Acute Tox. 2, H330 Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361; STOT RE 1, H372 | | |
| 7440-48-4 | cobalt | | 0.01% |
| | Resp. Sens. 1, H334; Carc. 2, H351 Skin Sens. 1, H317 | | |
























(Contd. on page 3)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

| | | (Contd. of page 2) |
|-----------|--|--------------------|
| 7440-50-8 | copper | 0.01% |
| 7439-89-6 | iron | 0.01% |
| 7440-09-7 | potassium | 0.01% |
| |  Water-react. 1, H260  Skin Corr. 1B, H314 | |
| 7439-93-2 | lithium | 0.01% |
| |  Water-react. 1, H260  Skin Corr. 1B, H314 | |
| 7439-95-4 | magnesium | 0.01% |
| |  Pyr. Sol. 1, H250; Water-react. 1, H260 | |
| 7439-96-5 | manganese | 0.01% |
| 7440-23-5 | sodium | 0.01% |
| |  Water-react. 1, H260  Skin Corr. 1B, H314 | |
| 7440-02-0 | nickel | 0.01% |
| |  Carc. 2, H351; STOT RE 1, H372  Skin Sens. 1, H317 | |
| 7723-14-0 | red phosphorus | 0.01% |
| |  Flam. Liq. 2, H225; Flam. Sol. 1, H228 | |
| 7439-92-1 | lead | 0.01% |
| |  Acute Tox. 3, H301  Carc. 2, H351; Repr. 1A, H360-H362  Acute Tox. 4, H332 | |
| 7782-49-2 | selenium | 0.01% |
| |  Acute Tox. 3, H301; Acute Tox. 3, H331  STOT RE 2, H373 | |
| 7440-24-6 | strontium | 0.01% |
| |  Water-react. 1, H260 | |
| 7440-28-0 | thallium | 0.01% |
| |  Acute Tox. 2, H300; Acute Tox. 2, H330  STOT RE 2, H373 | |
| 7440-61-1 | uranium | 0.01% |
| |  Acute Tox. 2, H300; Acute Tox. 2, H330  STOT RE 2, H373 | |
| 7440-62-2 | vanadium | 0.01% |
| 7440-66-6 | zinc | 0.01% |
| |  Water-react. 2, H261 | |
| 7440-38-2 | Arsenic | 0.01% |
| |  Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350 | |
| 7440-22-4 | silver | 0.01% |
| 7732-18-5 | Water | 94.75% |

USA

(Contd. on page 4)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT– 100mL

(Contd. of page 3)

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-----------|--------------------------|--------------------------|
| 7697-37-2 | Nitric Acid | 0.16 ppm |
| 7440-42-8 | boron | 1.9 mg/m ³ |
| 7440-39-3 | barium | 1.5 mg/m ³ |
| 7440-41-7 | beryllium | 0.0023 mg/m ³ |
| 7440-69-9 | bismuth | 15 mg/m ³ |
| 7440-43-9 | cadmium (non-pyrophoric) | 0.10 mg/m ³ |
| 7440-48-4 | cobalt | 0.18 mg/m ³ |
| 7440-50-8 | copper | 3 mg/m ³ |
| 7439-89-6 | iron | 3.2 mg/m ³ |

(Contd. on page 5)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

| (Contd. of page 4) | | |
|--------------------|----------------|------------------------|
| 7440-09-7 | potassium | 2.3 mg/m ³ |
| 7439-93-2 | lithium | 3.3 mg/m ³ |
| 7439-95-4 | magnesium | 18 mg/m ³ |
| 7439-96-5 | manganese | 3 mg/m ³ |
| 7440-23-5 | sodium | 13 mg/m ³ |
| 7440-02-0 | nickel | 4.5 mg/m ³ |
| 7723-14-0 | red phosphorus | 0.27 mg/m ³ |
| 7439-92-1 | lead | 0.15 mg/m ³ |
| 7782-49-2 | selenium | 0.6 mg/m ³ |
| 7440-24-6 | strontium | 30 mg/m ³ |
| 7440-28-0 | thallium | 0.06 mg/m ³ |
| 7440-61-1 | uranium | 0.6 mg/m ³ |
| 7440-62-2 | vanadium | 3 mg/m ³ |
| 7440-66-6 | zinc | 6 mg/m ³ |
| 7440-38-2 | Arsenic | 1.5 mg/m ³ |
| 7440-22-4 | silver | 0.3 mg/m ³ |

PAC-2:

| | | |
|-----------|--------------------------|-------------------------|
| 7697-37-2 | Nitric Acid | 24 ppm |
| 7440-42-8 | boron | 21 mg/m ³ |
| 7440-39-3 | barium | 180 mg/m ³ |
| 7440-41-7 | beryllium | 0.025 mg/m ³ |
| 7440-69-9 | bismuth | 170 mg/m ³ |
| 7440-43-9 | cadmium (non-pyrophoric) | 0.76 mg/m ³ |
| 7440-48-4 | cobalt | 2 mg/m ³ |
| 7440-50-8 | copper | 33 mg/m ³ |
| 7439-89-6 | iron | 35 mg/m ³ |
| 7440-09-7 | potassium | 25 mg/m ³ |
| 7439-93-2 | lithium | 36 mg/m ³ |
| 7439-95-4 | magnesium | 200 mg/m ³ |
| 7439-96-5 | manganese | 5 mg/m ³ |
| 7440-23-5 | sodium | 140 mg/m ³ |
| 7440-02-0 | nickel | 50 mg/m ³ |
| 7723-14-0 | red phosphorus | 3 mg/m ³ |
| 7439-92-1 | lead | 120 mg/m ³ |
| 7782-49-2 | selenium | 6.6 mg/m ³ |
| 7440-24-6 | strontium | 330 mg/m ³ |
| 7440-28-0 | thallium | 3.3 mg/m ³ |
| 7440-61-1 | uranium | 5 mg/m ³ |
| 7440-62-2 | vanadium | 5.8 mg/m ³ |
| 7440-66-6 | zinc | 21 mg/m ³ |

(Contd. on page 6)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

| | | (Contd. of page 5) |
|-----------------|--------------------------|-------------------------|
| 7440-38-2 | Arsenic | 17 mg/m ³ |
| 7440-22-4 | silver | 170 mg/m ³ |
| · PAC-3: | | |
| 7697-37-2 | Nitric Acid | 92 ppm |
| 7440-42-8 | boron | 130 mg/m ³ |
| 7440-39-3 | barium | 1,100 mg/m ³ |
| 7440-41-7 | beryllium | 0.1 mg/m ³ |
| 7440-69-9 | bismuth | 990 mg/m ³ |
| 7440-43-9 | cadmium (non-pyrophoric) | 4.7 mg/m ³ |
| 7440-48-4 | cobalt | 20 mg/m ³ |
| 7440-50-8 | copper | 200 mg/m ³ |
| 7439-89-6 | iron | 150 mg/m ³ |
| 7440-09-7 | potassium | 150 mg/m ³ |
| 7439-93-2 | lithium | 220 mg/m ³ |
| 7439-95-4 | magnesium | 1,200 mg/m ³ |
| 7439-96-5 | manganese | 1,800 mg/m ³ |
| 7440-23-5 | sodium | 870 mg/m ³ |
| 7440-02-0 | nickel | 99 mg/m ³ |
| 7723-14-0 | red phosphorus | 18 mg/m ³ |
| 7439-92-1 | lead | 700 mg/m ³ |
| 7782-49-2 | selenium | 40 mg/m ³ |
| 7440-24-6 | strontium | 2,000 mg/m ³ |
| 7440-28-0 | thallium | 20 mg/m ³ |
| 7440-61-1 | uranium | 30 mg/m ³ |
| 7440-62-2 | vanadium | 35 mg/m ³ |
| 7440-66-6 | zinc | 120 mg/m ³ |
| 7440-38-2 | Arsenic | 100 mg/m ³ |
| 7440-22-4 | silver | 990 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT– 100mL

· **Specific end use(s)** No further relevant information available.

(Contd. of page 6)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

| | |
|-----|--|
| PEL | Long-term value: 5 mg/m ³ , 2 ppm |
| REL | Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm |
| TLV | Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 7)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|--------------------------|-----------------|
| · Form: | Liquid |
| · Color: | Clear |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|---------------------------------------|-----------------|
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 100 °C (212 °F) |

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

| | |
|-----------------|-----------------|
| · Lower: | Not determined. |
| · Upper: | Not determined. |

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

| | |
|---------------------------|-----------------|
| · Density: | Not determined. |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

| | |
|---------------------|-----------------|
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |

· **Solvent content:**

| | |
|-----------------------|--------|
| · Water: | 94.8 % |
| · VOC content: | 0.00 % |

· **Solids content:** 0.2 %

· **Other information** No further relevant information available.

* 10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 9)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT– 100mL

(Contd. of page 8)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------------------|----|
| 7440-41-7 | beryllium | I |
| 7440-43-9 | cadmium (non-pyrophoric) | I |
| 7440-48-4 | cobalt | 2B |
| 7440-02-0 | nickel | 2B |
| 7439-92-1 | lead | 2B |
| 7782-49-2 | selenium | 3 |
| 7440-38-2 | Arsenic | I |

· **NTP (National Toxicology Program)**

| | | |
|-----------|--------------------------|---|
| 7440-41-7 | beryllium | K |
| 7440-43-9 | cadmium (non-pyrophoric) | K |
| 7440-48-4 | cobalt | R |
| 7440-02-0 | nickel | R |
| 7439-92-1 | lead | R |
| 7440-38-2 | Arsenic | K |

· **OSHA-Ca (Occupational Safety & Health Administration)**

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-38-2 | Arsenic |

USA

(Contd. on page 10)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT– 100mL

(Contd. of page 9)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of container and materials in accordance with local, regional and national regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|---|--|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN3264 |
| · UN proper shipping name | |
| · DOT | Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid) |
| · ADR | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid) |
| · IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 8 Corrosive substances |

(Contd. on page 11)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 10)

| | |
|--|--|
| · Label | 8 |
| · ADR | |
| | |
| · Class | 8 (C1) Corrosive substances |
| · Label | 8 |
| · IMDG, IATA | |
| | |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Corrosive substances |
| · Danger code (Kemler): | 88 |
| · EMS Number: | F-A,S-B |
| · Segregation groups | Acids |
| · Stowage Category | A |
| · Stowage Code | SW2 Clear of living quarters. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | |
| | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| · ADR | |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |

(Contd. on page 12)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 11)

· **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | | | |
|-----------|-------------|---|--------|
| 7732-18-5 | Water | | 94.75% |
| 7697-37-2 | Nitric Acid | Ox. Liq. 2, H272 Skin Corr. 1A, H314 | 5.0% |
| 7440-39-3 | barium | Water-react. 2, H261 | 0.01% |

· **Sara**

· **Section 355 (extremely hazardous substances):**

| | |
|-----------|----------------|
| 7697-37-2 | Nitric Acid |
| 7723-14-0 | red phosphorus |

· **Section 313 (Specific toxic chemical listings):**

| | |
|-----------|--------------------------|
| 7697-37-2 | Nitric Acid |
| 7440-39-3 | barium |
| 7440-41-7 | beryllium |
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-48-4 | cobalt |
| 7440-50-8 | copper |
| 7439-96-5 | manganese |
| 7440-02-0 | nickel |
| 7723-14-0 | red phosphorus |
| 7439-92-1 | lead |
| 7782-49-2 | selenium |
| 7440-28-0 | thallium |
| 7440-62-2 | vanadium |
| 7440-66-6 | zinc |
| 7440-38-2 | Arsenic |
| 7440-22-4 | silver |

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

| | |
|-----------|-------------|
| 7697-37-2 | Nitric Acid |
| 7440-42-8 | boron |
| 7440-39-3 | barium |
| 7440-41-7 | beryllium |
| 7440-69-9 | bismuth |
| 7440-70-2 | calcium |

(Contd. on page 13)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 12)

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-48-4 | cobalt |
| 7440-50-8 | copper |
| 7439-89-6 | iron |
| 7440-09-7 | potassium |
| 7439-93-2 | lithium |
| 7439-95-4 | magnesium |
| 7439-96-5 | manganese |
| 7440-23-5 | sodium |
| 7440-02-0 | nickel |
| 7723-14-0 | red phosphorus |
| 7439-92-1 | lead |
| 7782-49-2 | selenium |
| 7440-24-6 | strontium |
| 7440-28-0 | thallium |
| 7440-61-1 | uranium |
| 7440-62-2 | vanadium |
| 7440-66-6 | zinc |
| 7440-38-2 | Arsenic |
| 7440-22-4 | silver |
| 7732-18-5 | Water |

· Proposition 65

· Chemicals known to cause cancer:

| | |
|-----------|--------------------------|
| 7440-41-7 | beryllium |
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-48-4 | cobalt |
| 7440-02-0 | nickel |
| 7439-92-1 | lead |
| 7440-38-2 | Arsenic |

· Chemicals known to cause reproductive toxicity for females:

| | |
|-----------|------|
| 7439-92-1 | lead |
|-----------|------|

· Chemicals known to cause reproductive toxicity for males:

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7439-92-1 | lead |

· Chemicals known to cause developmental toxicity:

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7439-92-1 | lead |

(Contd. on page 14)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT- 100mL

(Contd. of page 13)

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

| | | |
|-----------|--------------------------|-------------------------|
| 7440-42-8 | boron | I (oral) |
| 7440-39-3 | barium | D, CBD(inh), NL(oral) |
| 7440-41-7 | beryllium | B1, K/L(inh), CBD(oral) |
| 7440-43-9 | cadmium (non-pyrophoric) | B1 |
| 7440-50-8 | copper | D |
| 7439-96-5 | manganese | D |
| 7723-14-0 | red phosphorus | D |
| 7439-92-1 | lead | B2 |
| 7782-49-2 | selenium | D |
| 7440-66-6 | zinc | D, I, II |
| 7440-38-2 | Arsenic | A |
| 7440-22-4 | silver | D |

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|-----------|--------------------------|----|
| 7440-39-3 | barium | A4 |
| 7440-41-7 | beryllium | A1 |
| 7440-43-9 | cadmium (non-pyrophoric) | A2 |
| 7440-48-4 | cobalt | A3 |
| 7440-02-0 | nickel | A5 |
| 7439-92-1 | lead | A3 |
| 7440-61-1 | uranium | A1 |
| 7440-38-2 | Arsenic | A1 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

| | |
|-----------|--------------------------|
| 7440-41-7 | beryllium |
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-02-0 | nickel |
| 7440-61-1 | uranium |
| 7440-38-2 | Arsenic |

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made

(Contd. on page 15)

acc. to OSHA HCS

Printing date 07/18/2018

Review date 07/18/2018

Trade name: STANDARD 25 MULTI-ELEMENT– 100mL

(Contd. of page 14)

concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· *** Data compared to the previous version altered.**