

Spectrum 3 FT-IR Spectrometers

Infrared Spectroscopy



Spectrum 3 FT-IR with UATR

Introduction

The PerkinElmer Spectrum 3™ is the gold standard in FT-IR and FT-NIR spectrometers, enabling laboratories to obtain the highest quality and most reproducible data with exceptional ease. A broad range of “plug-and-go” sampling accessories and software packages ensure the best solution for a range of applications. Whatever your specific laboratory requirements, the Spectrum 3 delivers best-in-class accuracy, precision and reliability ensuring the utmost confidence in your results.

PerkinElmer Spectrum 3 FT-IR spectrometers are built to the highest ISO-9001 manufacturing standards. This document presents technical information and typical performance specifications for the Spectrum 3 FT-IR instruments based on recent factory tests.

OPTICAL PERFORMANCE			
Wavelength Range	8,300 – 350 cm ⁻¹ optimized, proprietary KBr beamsplitter 7,800-225 cm ⁻¹ with Csl beamsplitter option	11000 – 375 cm ⁻¹ with proprietary extended range, dual source option	For dedicated optimised NIR operation, the Spectrum 3 FT-NIR and dual range NIR/MIR is available. See separate technical specification sheet for details
Spectral Resolution	0.4 cm ⁻¹ for the 3028 cm ⁻¹ band in Methane		
Wavenumber Accuracy	0.02 cm ⁻¹ at 2,000 cm ⁻¹		
Signal-to-Noise	10,000:1 peak-peak, 5 seconds 34,000:1 peak-peak, 1 minute		15000:1 peak-peak, 5 seconds 50,000:1 peak-peak, 1 minute with high performance
Wavelength Repeatability			
Mid-IR	±0.02 cm ⁻¹ at 1,600 cm ⁻¹		±0.007 cm ⁻¹ achievable
Near-IR	±0.02 cm ⁻¹ at 7,200 cm ⁻¹ (±0.004 nm at 1,390 nm)		
OPTICAL SYSTEM			
General	Sealed and desiccated optical unit. Vibration isolated baseplate.		
Interferometer	Improved rotary Michelson interferometer for fast scanning, self-compensating for dynamic alignment changes due to a tilt and shear, incorporating high reflectivity, first-surface aluminum-coated optics.		
Optics	Kinematically mounted, zero alignment optics.		
Mirrors	High reflectivity and a low-angle off axis design.		
Detectors	Capabilities for two permanently installed internal detectors, plus external detector via General Purpose Optical Bench (GPOB). Single software click to switch active detectors. For internal detectors, choose from: <ul style="list-style-type: none"> • High linearity Lithium tantalate • Fast-recovery FR-DLTGS • Mercury cadmium telluride (MCT) 		
Source	Long-life source with proprietary hot-spot stabilization. User replaceable.		
Beamsplitter	<ul style="list-style-type: none"> • Standard optimised KBr • Extended range KBr option • Extended range Csl option 		
Desiccant	Accepts disposable packs or rechargeable desiccant cartridges. Visible desiccant lifetime indicator.		
External Beam Ports	Optional external beam ports providing 2 additional output plus 1 additional input beam.		
General Purpose Optical Bench (GPOB)	Optional optical bench available for custom accessories and detectors.		
Validation	Software controlled validation wheel containing a polystyrene reference material, traceable to a NIST standard for wavenumber accuracy and a Schott NG11 filter for ordinate repeatability.		
Full Optical Upgradeability	Single range Spectrum 3 systems can be upgraded to multi-range IR/NIR or IR/FIR optical benches.		
DATA SYSTEM AND ELECTRONICS			
Signal Sampling	Over-sampling delta-sigma converter.		
Communication	TCP/IP interface allows direct connection with LAN. Instruments can be configured with their own IP address allowing control via the internet.		
Calibration Transfer	Optional Absolute Virtual Instrument (AVI) – actively standardizes instrument response to further improve repeatability and protect data integrity.		
Atmospheric Compensation	Minimizes effect of atmospheric water and CO ₂ on the sample spectra without the need for reference or calibration spectra. Operates at various instrument settings without having to recalibrate the correction.		
Accessory Recognition	Spectrum 3 accessories and ATR top plates are automatically detected as soon as they are locked into the sampling area. Instrument parameters are optimized for the installed accessory. Serial numbers for accessories and top plates are stored with all data.		
Error Trapping	All sample spectra are checked for common spectroscopic and sampling problems. Key instrument components are continuously monitored.		
Productivity	<ul style="list-style-type: none"> • Spectrum 3 Smart Panel allows at-bench view of diagnostics and instrument control in addition to standard PC or panel PC control. • Look-ahead function automatically detects when a sample is placed into the sample compartment. Data is collected while the operator is entering sample information. • On-instrument remote user interface and software Sample Table allows remote, continuous sampling at the instrument eliminating analysis steps and speeding operation. 		

BENCH DETAILS	
Size	520 mm x 600 mm x 300 mm (W x D x H).
Weight	34 kg
SOFTWARE	
General	A single software platform incorporates all of the functions required for infrared analyses; instrument control, data manipulation and analysis, and flexible report utilities. A suite of optional software packages provide advanced capabilities or functions designed for specific application areas.
Sample Table	Increases productivity by enabling multiple samples to be defined in batches. Integrates with SmartPanel allowing remote continuous operation.
User Interface	Password-protected user login function. Access to methods and routines, menu, toolbar and toolbox functions can be controlled by a supervisor.
Reports	Quick print facility for graphs, spectra and results windows. User defined templates can be created to enable custom printed and electronic reports.
Processing	1st-4th derivative with a variable filter, smooth (Savitsky-Golay, moving average and triangular), difference, normalization, A, %T, %R, KM, LOG (1/R), ordinate modes, cm ⁻¹ , nm and micron abscissa modes, +, -, *, /, difference, baseline correction, smooth, deconvolution, normalize, interpolate, blank, Kramers-Kronig, advanced ATR correction, peak table, peak height and peak area.
Materials Testing	Patented COMPARE™ spectral comparison algorithm and Euclidean searching. Spectral searching against commercially available or customer-developed libraries. Multi-component search option for up to 10 components. Advanced ATR preprocessing options to allow improved searching of ATR spectra against transmission libraries.
Quantitative Analysis	Single frequency, method development software. Includes Beer's Law, PLS and PCR quantitative prediction.
Adulterant Screening	Unique chemometrics-based approach to estimation of adulterants in spectra. Simple method development requires just typical pure spectra and spectra of potential adulterants.
Validation	Instrument performance and user configurable system suitability routines available as standard. Instrument Scheduler facility allows auto-programming of instrument validation testing.
Macros	Macro Editor and Equations Editor provide the ability to setup sequences of data collection and custom spectral processing. These procedures can then be stored and repeated using a single mouse click. Simple user-interface development designed for Touchscreen PC interaction - Spectrum Touch software option.
User Training	Use, common maintenance and software operation. Context-sensitive help provides assistance throughout the software.
Further Optional packages	
21 CFR Part 11	Enhanced Security™ (ES) software meets the technical requirements for the FDA's 21 CFR Part 11.
Cloud Connectivity	PerkinElmer NetPlus for IR option allows operators within organisations to collaborate by securely sharing IR data, methods and more via the cloud.
Sample Analysis Workflows	AssureID™ software designed for FT-IR and FT-NIR materials testing and product verification. Supports Mid-IR and NIR products testing through a customizable wizard-style interface. Simple turnkey Compare, SIMCA, quantitative analyses with user defined instructions and reports can be readily configured. OLE-DB compliant data storage with ES and non-ES versions available.
Quantitative Analysis	Optional method development software for PLS and PCR quantitative method development.
Validation CD	Data validation CD contains test algorithm descriptions, test data and results for data transform algorithms. Comprehensive UOQ/IQ/OQ documentation and services available.

PerkinElmer, Inc.
 940 Winter Street
 Waltham, MA 02451 USA
 P: (800) 762-4000 or
 (+1) 203-925-4602
www.perkinelmer.com



For a complete listing of our global offices, visit www.perkinelmer.com/ContactUs

Copyright © 2020, PerkinElmer, Inc. All rights reserved. PerkinElmer® is a registered trademark of PerkinElmer, Inc. All other trademarks are the property of their respective owners.

007457F_07